

Rated voltage (V.DC)	Surge voltage (V.DC)	Rated capacitance (μF)	Max ripple current 85°C 120Hz (A)	Size φD×L(mm)
80	100	10000	4.2	φ 35×80
		15000	6.0	φ 35×120
		22000	6.5	φ 51×80
		33000	9.2	φ 51×120
		47000	12.7	φ 65×100
		68000	15.5	φ 65×140
		100000	21.3	φ 76×140
		150000	26.5	φ 89×170
100	125	220000	28.9	φ 89×220
		4700	3.8	φ 35×80
		6800	4.5	φ 35×100
		10000	5.3	φ 35×120
		15000	6.0	φ 51×80
		22000	6.8	φ 51×100
		33000	10.0	φ 51×140
		47000	14.4	φ 65×140
160	200	68000	18.2	φ 76×140
		100000	22.1	φ 89×170
		150000	27.0	φ 89×220
		4700	3.2	φ 35×80
		6800	4.7	φ 35×120
		10000	5.0	φ 51×80
		15000	6.4	φ 51×100
		22000	9.1	φ 65×100
200	250	33000	12.0	φ 76×140
		47000	16.9	φ 89×170
		68000	19.2	φ 89×220
		1500	2.9	φ 35×80
		2200	3.5	φ 35×100
		3300	4.8	φ 51×80
		4700	6.3	φ 51×100
		6800	7.3	φ 51×140
250	300	10000	9.8	φ 65×120
		15000	13.0	φ 76×120
		22000	15.9	φ 89×140
		33000	19.5	φ 89×170
		47000	20.9	φ 89×220
		1000	2.4	φ 35×80
		1500	3.0	φ 35×100
		2200	4.0	φ 51×80
250	300	3300	5.4	φ 51×100
		4700	7.3	φ 65×100
		6800	8.9	φ 65×120
		10000	11.8	φ 76×120
		15000	16.4	φ 89×140
		22000	17.9	φ 89×170
		33000	19.7	φ 89×220

\*额定纹波电流I<sub>r</sub>~ Rated ripple current (+85°C,100Hz或 120Hz)